

Wipe Out Graffiti Remover – Specification and Data

PRODUCT

Wipe Out Porous Surface Graffiti Remover

Manufacturer

Dumond Chemicals
1501 Broadway
New York, NY 10036
(212) 869-6350
web: www.dumondchemical.com
e-mail: plaway@aol.com

PRODUCT DESCRIPTION:

Watch Dog™ WIPE OUT® Graffiti Remover is specifically formulated for use on porous surfaces and will not damage surfaces including brick, concrete, cement, pavers, stone and terrazzo. Environmentally-friendly, WIPE OUT® works well on spray paint, marker, pen, ink, crayon, shoe polish, lipstick and most other graffiti marks and stains.

FEATURES & BENEFITS:

- Safe, Non-Drip, Environmentally Friendly Formulation
- Single Application, Easy Removal of Existing Graffiti
- Effective on Most Porous Surfaces...Without Damaging Them!
- Removes Adhesives, Paint Spills, Caulking, Epoxies, and Urethanes

TEST AREA:

ALWAYS TEST each type of surface to determine compatibility, application techniques and thickness, dwell time, and satisfactory results before overall application.

HOW TO USE:

Wear eye protection, rubber or latex gloves.
1. Apply product liberally, at full strength, using a brush, roller or sprayer (HVLP).
2. Allow product to remain on surface for approximately 15 – 20 minutes to penetrate the graffiti. **3.** Power wash with 15° tip ..1000/2500

psi max. **4.** Repeat process if necessary.

ALTERNATE: Allow to penetrate for 30 – 35 minutes, agitate with scrub brush, and remove with water hose.

COVERAGE:

Approximately 100 – 150 sq. ft. per gallon, depending upon porosity of surface.

AVAILABILITY & COST: Watch Dog™

products are available through a nationwide network of paint and hardware stores, and construction and safety supply distributors. For the outlet nearest you, call 800/245 -1191 or email plaway@aol.com.

LIMITED WARRANTY:

The manufacturer and distributors liability under any express or implied warranty is limited solely to replacement of product that is defective or refund of the purchase price. Claims must be made within one year of purchase and be accompanied with proof of purchase. The manufacturer and distributors shall not be liable for injury, labor or any consequential damages.

TECHNICAL SERVICES: Dumond's expert staff is available to answer technical questions and provide product-specific information required by architects, specifiers, contractors and property owners. Expert, on-site assistance is available at no additional cost. Call 800/245-1191 or email plaway@aol.com with product or technical questions

Technical Data:

Form: Gel
Flash Point: Over 200°F
WT/GAL: 8.9 lb./gal